

CANEXEL

SUMMARY TECHNICAL INFORMATION SHEET

Siding element range	CED'R-TEX	RIDGEWOOD ULTRA-PLANK
Composition	95% wood fibres, 3% wax, 2% phenol resin	
Board	Single board with tongue	Double board with incurved channel (Ridgewood) or rectangular channel (Ultra-Plank)
Appearance	Wood relief	
Finishing	4 coats of UV-resistant acrylic paint baked in ovens at 160°	
Colour	White, Almond, Sand, Mist grey, Scottish blue, Acadia, Yellowstone, Sierra, Cream, Granite, Dutch green, Khaki	White, Almond, Sand, Mist grey, Scottish blue, Acadia, Yellowstone, Sierra. Additional Ridgewood colours: Country red, Cedar, Cream, Granite, Dutch green, Khaki
Effective width x length x thickness	3657 x 200 x 8.8 mm	3657 x 280 x 10 mm
Installation	By overlap horizontally	By conformation fitting horizontally, vertically and diagonally for Ridgewood, only vertically for Ultra-Plank
Fixing	Concealed by nailing every 400 mm	
Effective surface per bundle	4 siding elements = 2.91 m ²	4 siding elements = 4.10 m ²
Effective surface per pallet	40 bundles = 116.40 m ²	27 bundles = 110.70 m ²
Weight per unit of surface area	10.6 kg/m ²	10.3 kg/m ²
Density	920 kg/m ³	920 kg/ m ³
Guarantee and certifications	Ten year guarantee SMABTP no. 285425V Fire reaction Rating M3 – Test Report no. E021068-CEMAT/1 CSTB Technical Assessment no. 2/03-1037	
ReVETIR rating	r2e2V2E3T3I2R4	r2e2V1E3T3I2R4
Strength and resistance tests	Good ageing stability, attested by Bureau Veritas Tests of isotropy, of moisture resistance, temperature differences, impacts, Earthquakes, by CSTB	
Servicing	Minimised servicing. Dirty surfaces can be cleaned with water and non-abrasive detergent.	